



STRIDER~RESOURCE

New & Innovative Products & Processes for the Lifting, Rigging & Load Securement Industry™



Industry First!

Maneuverable LED Swager Work Light


Universal Die Pocket accommodates both One Press® and multi press dies.

Dies bolt quickly and securely into place.

Die pocket rotates 360° for easy access and ergonomic positioning.

Covered electronic foot pedal allows the operator full manual control of the swaging action.

1100 Ton Universal™ Swagers



Multi-directional warning light indicates to others that the swager is on.

Safe use guides.

Conveniently located pressure valve and oversized gauge for improved visibility and accuracy.

Pump is fully enclosed and insulated for exceptionally quiet operation.

Maximum Pressure Capacity	1,100 tons	10,000 kN
Maximum Oil Pressure	5,000 psi	350 bar
Maximum Piston Stroke	3.75 inches	95 mm
Maximum Swager Speed	0.4 inches per second	10 mm per second
Minimum Swager Speed	0.04 inches per second	1 mm per second
Dimensions (HxWxD)	90.375" x 77.125" x 55.75"	2,295 mm x 1,959 mm x 1,416 mm
Working Height	46 inches	1,168 mm
Weight	13,228 lbs	6,000 kg
Power Supply	460 V - 3 PH - 60 Hz - 20 HP	Other voltages on request
Oil Capacity	53 gallons	200 liters

Produced in accordance with the CE machinery directive & BS EN 693:2001



The One Press® Swaging System is the fastest and most reliable method of swaging Flemish eye wire rope slings and assemblies. One Press® single stage dies swage carbon steel One Press® sleeves from 1/4" up to 1-1/2" completely in just one press, significantly reducing exposure to hazards.

U.S. Patents #5,816,094 & #6,032,338, Canadian Patent #2,172,267, and other International Patents.

Contact Strider~Resource today to learn more about Safeguarding.

Phone: +1 (905) 859.3901 Email: service@strider-resource.com Website: www.strider-resource.com