
PIAB OVERLOAD GUARD & SLACK LINE SWITCH

PRICE GUIDE & ORDERING INFORMATION

The price of an LKV Overload Guard and Slack Line Switch varies according to model. Choose the **LKV** model that has a switch range that will accommodate the single line part value of the crane or hoist. To obtain the single line part value when used as an **Overload Guard**, divide the rated capacity of the crane or hoist by the number of line parts. To obtain the single line part value when used as a **Slack Line Switch**, divide the tare value by the number of line parts.

EXAMPLE: The single line part value of a 10 ton crane with 4 line parts is 2.5 tons or 5000 lbs. The appropriate **LKV** would then be set at 5000 lbs. when used as an Overload Guard

The appropriate LKV model for a 10 ton crane with 4 line parts is an LKV 4, with a switch range of 880-8,800 lbs. for a single line part to accommodate the single line part value of 5,000 lbs. An LKV 2 is unsuitable since it has a maximum switch value of only 4,400 lbs. versus the required 5,000 lbs. The same LKV 4 can also be used on a crane with 4 parts of line to a maximum of 16 tonne or 35,200 lbs., or a maximum of 24 tonne or 52,800 lbs. with 6 parts of line, etc.



						MEASUREMENTS IN INCHES			
MODEL	SWITCH RANGE LBS.	ROPE DIAMETER GUIDE SIZES	UNIT WT. POUNDS	Length Pin/Pin	O/A Length	O/A Width	Thick-	PRICE EACH †	
LKV 01	90 - 220			7.78	10.5	5.59	2.36		
LKV 1	220 - 2,200	3/16-1/4-5/16" (5-8mm) 5/16-3/8-7/16" (8-12mm)							
LKV 2	440 - 4,400	1/2-9/16-5/8" (12-16mm) 5/8 - 3/4" (16-20mm)							
LKV 4	880 - 8,800	370 371 (10-20mm)							
LKV 08	440 - 2,425	5/8 - 3/4" (16-20mm)	26.5	11.8	15.86	8.19	3.39		
LKV 8	1,760 - 17,600	3/4 - 7/8" (20-24mm) 1 - 1-1/8" (24-28mm)							
LKV 12	2,645 - 26,400	1-1/8 - 1-1/4" (28-32mm) 1-1/4 - 1-3/8" (32-36mm)							
LKV 16	3,525 - 35,200	1-3/8 - 1-1/2" (36-40mm) 1-1/2 - 1-3/4" (40-44mm)	48.5	18.9	23.62	8.46	5.32		

† PRICE INCLUDES:

Installation WrenchAdjustment Wrench

Locking Device13 Ft. of Cable

. Switch Value Setting

. Wiring Diagram

. Certification & Traceability

. Installation Instructions

GUARANTEE: All LKV models are guaranteed to be free from defects in material and workmanship for 5 years from the date of shipment to the customer.

When ordering please specify:

- The rated capacity of the crane or hoist in tons or tonnes (pounds or kilograms) when used as an Overload Guard
 The tare value or the weight of the hook block and tackle, when used as a Slack Line Switch.
- 2. The number of wire rope line parts (falls) including the stationary line.
- 3. The nominal wire rope size in inches or millimeters.
- 4. The shut-off value if to be set for a value other than for the rated capacity, or for the tare value.
- 5. Rated capacity of the wire rope if the crane or wire rope has been modified from the original installation.
- 6. The general application, including minimum headroom available.