SmartTM Swager available with Swager GuardingTM



Swager GuardingTM allows trained operators to swage wire rope slings without risk of injury caused by pinch points. New and innovative technology permits a full range of wire rope diameters to move freely within the swaging zone. The system automatically stops when the operator gets too close, and easily resets to continue swaging.

The SmartTM **Swager** incorporates a universal die pocket to accommodate both One Press® and multi-press dies which are quickly and easily installed using a modern reliable eccentric clamping system. The pump and motor are fully enclosed and insulated. The swager operates at a very low noise level of 60-68 decibels. The main controls and the electric foot pedal can be repositioned for easy accessibility.

The control system counts and records the total number of swages and operational hours. It records overloads and provides maintenance alerts. Alarms indicate if the oil level is low and if the oil and filter needs to be changed.

Stroke limiter and hold modes are easily programmed to save time and energy.

Max. Pressure Capacity	660 Tonnes / 600 Tons
Max. Piston Stroke	60 mm
Unloaded Stroke Speed	9.5 mm/second
Power Supply	220V, 3phase, 60HTz
Dimensions L*W*H (mm)	2,065 x 910 x 1,940
Weight	2,600 kg / 5,732 lb

The One Press® Swaging System

The fastest and most reliable method of swaging Flemish eye wire rope slings and assemblies in the world. Swage Carbon Steel Sleeves from 1/4" up to 1-1/2" in just One Press®!

US Patents #5,816,094 & #6,032,338 Canadian Patent #2,172,267

For more information contact Strider~Resource: 5667 King Road, Nobleton, ON, Canada, L0G 1N0 phone: 905.859.3901 fax: 905.859.4345 email: service@strider-resource.com www.strider-resource.com